

IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION **IEC Certification System for Explosive Atmospheres**

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEx IBE 15.0015

Page 1 of 4

Certificate history:

Status:

Current

Issue No: 1

Issue 0 (2016-03-10)

Date of Issue:

2020-12-18

Applicant:

Adolf Schuch GmbH, Lichttechnische Spezialfabrik

Mainzer Str. 172, 67547 Worms

Germany

Equipment:

LED-Light Fitting type nD866...L... and LED Emergency Light Fitting type nD867...L...

Optional accessory:

Type of Protection:

increased safety in combination with flameproof enclosure, powder filling, encapsulation and intrinsic safety

or protection by enclosure

Marking:

Type nD 866...L... Ex ec IIC T4 Gc Ex ec a IIC T4 Gc Ex db ec IIC T4 Gc Ex ec ib mb IIC T4 Gc Ex tc IIIC T80 °C Dc

-30 °C ≤ T_{amb} ≤ +65 °C (maximum values)

Type nD 867...L... Ex ec IIC T4 Gc Ex db ec IIC T4 Gc Ex to IIIC T80 °C Dc

-30 °C ≤ T_{amb} ≤ +55 °C (maximum values)

Approved for issue on behalf of the IECEx Certification Body:

Alexander Henker

Position:

Signature:

(for printed version)

Date:

Deputy Head of department Certification Body

2020-12-18

This certificate and schedule may only be reproduced in full.

This certificate is not transferable and remains the property of the issuing body.

The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

IBExU Institut für Sicherheitstechnik GmbH Fuchsmühlenweg 7 09599 Freiberg Germany





IECEx Certificate of Conformity

Certificate No.:

IECEx IBE 15.0015

Page 2 of 4

Date of issue:

2020-12-18

Issue No: 1

Manufacturer:

Adolf Schuch GmbH, Lichttechnische Spezialabrik

Mainzer Str. 172, 67547 Worms

Germany

Additional manufacturing locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS:

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017

Explosive atmospheres - Part 0: Equipment - General requirements

Edition:7.0

IEC 60079-1:2014-06 Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"

Edition:7.0

IEC 60079-11:2011

Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"

Edition:6.0

IEC 60079-18:2017 Explosive atmospheres - Part 18: Protection by encapsulation "m"

Edition:4.1

IEC 60079-31:2013 Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"

Edition:2

IEC 60079-5:2015

Explosive atmospheres -Part 5: Equipment protection by powder filling "q"

Edition:4.0

IEC 60079-7:2017

Edition:5.1

Explosive atmospheres - Part 7: Equipment protection by increased safety "e"

This Certificate does not indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Reports:

DE/IBE/ExTR15.0039/00

DE/IBE/ExTR15.0039/01

Quality Assessment Report:

DE/PTB/QAR09.0004/05



IECEx Certificate of Conformity

Certificate No.:

IECEx IBE 15.0015

Page 3 of 4

Date of issue:

2020-12-18

Issue No: 1

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

The LED-Light Fitting type nD866...L... and LED Emergency Light Fitting type nD867...L... are used to illuminate factory and depot sites in areas with potentially gas and dust explosive requiring equipment of EPL Gc or Dc. The luminaire consists of a polyester enclosure with fasteners made of stainless steel, a reflector with assembled LED boards, LED control gear and terminals, as well as a light-transmitting cover made of polycarbonate.

LED Emergency Light Fitting type nD867...L... provides an emergency light function. It uses an alternate LED control gear and a rechargeable and changeable battery pack in difference to type nD866. The battery pack is either in the housing or in a separate battery housing which is assembled to the side of the luminaire. Service and fault conditions are indicated by means of coloured LED which is inside the luminaire.

The output current for supplying the LED modules may be set by means of DALI interface. Both types may be equipped with coloured LED.

Technical data:

Rated voltage:	nD866: 220 240 V AC (5060 Hz) or 176 275 V DC nD867: 220 240 V AC (5060 Hz)
Input power:	nD866: up to 54 W (typically) nD867: up to 41 W (typically)
Battery:	NiCd 6 V / 4 Ah NiCd 6 V / 1.6 Ah
Through-wiring / looping:	up to 12 x ≥ 2.5 mm² (max. 4 x 16 A)
Ambient temperature range:	-30 °C+65 °C

These values are maximum values. The actual values are determined by the built-in components. The manufacturer specified the rated values in the context of these limiting values and ensures compliance with the maximum surface temperature of the equipment and the permissible operating temperature of the components. Through-wiring, selection of cable and cable glands may be restricted in some types of the luminaire

SPECIFIC CONDITIONS OF USE: NO



IECEx Certificate of Conformity

Certificate No.:

IECEx IBE 15.0015

Page 4 of 4

Date of issue:

2020-12-18

Issue No: 1

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)

- A LED Emergency Light Fitting type nD867...L... has been added.
 A new housing has been added.
- The luminaires may be manufactured of alternate plastic materials.
- The use of new components has been assessed.
- The luminaire complies with the requirements of the current standards. Thus the marking has been changed.