LED emergency light fitting


161 06L20 AUS ZB


[Item no. : 16118 0061]



General product description


Sturdy LED damp-proof light fitting for unprotected outdoor areas for connection to central power supply systems with incorporated fuse for selective disconnection in case of failure. Highly impact-resistant glass fibre reinforced polyester housing and frosted diffuser with high impact resistance and UV resistance. Captive clips, multi-part, incl. two safety clips, silicone gasket and pressure compensation system. Powder-coated aluminium reflector with highly efficient Zhaga LED modules and ECG with overload and short circuit protection.





General product benefits

- sturdy, extremely reliable high-quality light fitting for application in unprotected outdoor areas
- high impact resistant housing, chemical and UV resistant
- diffuser with high mechanical and UV-resistance
- UV, ozone, weather, chemical and ageing resistant profile gasket
- pressure compensation system to prevent condensation inside the light fitting
- 100% luminous flux even in emergency operation
- highly efficient by using high-quality ECG and LED modules
- homogenous illumination due to frosted diffuser, comfortable perception of light and brilliant glare limitation
- interchangeable components
- future proof by using standardised Zhaga LED modules



Applications

- humid, wet and dusty indoor areas and sheltered outdoor areas as replacement lighting in the event of a power failure, or as safety lighting to illuminate escape and rescue routes
- unprotected outdoor areas, e.g. mounted to industrial plants, external gangways, stairs, walls, ceilings, doors, bus stops, train stations,subways, construction sites, under canopies etc. The light is not to be used in areas with high mechanical stress (wind) or seldom usage (i.e. maintenance and inspection only).

161 06L20 AUS ZB

[Item no. : 16118 0061]

Technical data

General

EAN/GTIN:	4041254295312

Emergency lighting

Emergency power supply:	central supply (ZB)
Operating mode:	Maintained mode
DC level (ZB/central battery):	100 %
Inrushcurrent:	21 A
Peak:	126 µs

Key technical data

Light source:	LED
LED module standard:	Zhaga
Exchangeability:	light source and control gear replaceable by qualified person
Connected load:	16 W
Luminaire luminous flux:	2370 lm
Luminous efficacy:	148 lm/W
Colour temperature:	4000 K
Colour rendering (CRI):	≥ 80
Light colour:	840
Admissible ambient temperature T_a:	-20 °C to +40 °C
Control gear:	1 x ECG, Overload protection, Short circuit protection
I LED max:	300 mA

Lighting technology

Light distribution:	symmetrical wide beam
Beam angle:	120 °
Photobiological safety:	RG1

Service life

Service life LED:	L90>50000 h (@ Ta 25°C), L80>70000 h (@ Ta max), L70>100000 h (@ Ta max)

Electrical connection

Rated voltage:	220 - 240 V, 0 Hz, 50/60 Hz
Terminal clamp:	Cage clamp, 3-polig, 0,75 - 2,5 mm²
Max. no. with circuit breaker B16:	36
CB B10/B13/B20:	23/30/46
CB C10/C13/C16/C20:	37/48/61/74
Cable entries:	M20 (2x), pressure compensation element (1x), cable gland (1x), Plastic, 6 - 13 mm

Features/Certificates

Protection class:	I

Features/Certificates

IP rating:	IP65
IK rating:	IK05
Limited surface temperature D:	Yes
Approval marks:	CE

Mounting

Mounting method (accessories possibly needed):	Ceiling, Wall, Ceiling with bracket, Ceiling with angle, Suspended, Mounting rail, Wall with bracket, Wall with angle
Operating position:	downwards radiation, forwards radiation, horizontal
Mounting:	2-point

Housing

Housing material:	Glass fibre reinforced polyester
Colour:	grey

Cover

Cover type / material:	Diffuser (PMMA)
Cover characteristic:	satined
Closure:	Clips (Plastic)

Other features

Pressure compensation system:	Yes

Dimension/Weight

Length:	662.00 mm
Width / Diameter:	116.00 mm
Height:	125.00 mm
Net weight:	1.59 kg

161 06L20 AUS ZB

[Item no. : 16118 0061]

Optional accessories / spare parts

Item no.	Item name	Item description
16111 9035	ABD 161 018 F	cover PMMA frosted
16111 9031	ABD 161 036 F	cover PMMA frosted
16111 9032	ABD 161 058 F	cover PMMA frosted
16111 9036	ABD 161 018 F PC	cover PC frosted
16111 9033	ABD 161 036 F PC	cover PC frosted
16111 9034	ABD 161 058 F PC	cover PC frosted
16111 9017	ABD 161 018 LM	cover high chemical resistant clear IFS
16111 9018	ABD 161 036 LM	cover high chemical resistant clear IFS
16111 9019	ABD 161 058 LM	cover high chemical resistant clear IFS
90004 0001	SK 120	wire guard powder coated for 161 06..
90004 0002	SK 140	wire guard powder coated for 161 12..
90004 0003	SK 165	wire guard powder coated for 161 15..
90053 9008	KK/KKS FR VE10	locking clips (10 pcs.) with 2 safety clips
90055 9004	KE/KES VE10	locking clips (10 pcs.) with 2 safety clips
90053 9004	KKS FR P	safety clips (1 pair)
90055 9005	KES P	safety clips (1 pair)
90063 9000	2511	blanking plug M20
25610 9000	2561	cable gland M20
25600 9000	2560	cable gland M25
90259 9002	DAE20	breather M20
90259 9003	DAE20/25	breather M20 with extension M25
90093 0002	183 RO 112 A P	2 pipe clamps 1 1/2", stainless steel, with support
90094 0002	183 RO 2 A P	2 pipe clamps 2", stainless steel, with support
90045 9001	HW 30 P	wall and ceiling mounting (1 pair) aluminium 30°
90045 9002	HW 45 P	wall and ceiling mounting (1 pair) aluminium 45°
90045 9004	HW 60 P	wall and ceiling mounting (1 pair) aluminium 60°
90045 9003	HW 90 P	wall and ceiling mounting (1 pair) aluminium 90°
90049 0002	183 S	hook stainless steel for chain mounting
90095 0001	DS 183	ceiling rail stainless steel with M5 screw