
LED damp-proof light fitting

PROXIMA
161PX 15L VARIO AUS
[Item no. : 16131 0091]




General product description

Sturdy LED damp-proof light fitting with variably adjustable luminous flux for application in unprotected outdoor areas. Highly impact-resistant glass fibre reinforced polyester housing and frosted diffuser with high mechanical resistance. Captive safety clips, multi-part, silicone gasket. Powder-coated aluminium reflector with highly efficient Zhaga LED modules and ECG with overload and short circuit protection and switch for toolless setting of the luminous flux. FastFix mounting system with sliding stainless steel mounting clips and brackets for chain suspension.



General product benefits

- universally usable due to variable setting of the luminous flux depending on the requirement (replaces fluorescent lamps from 1x36W up to 2x58W)
- high flexibility due to almost infinitely variable luminous flux setting
- quick and easy adjustment on-site
- adjustable at any time (e.g. change of use of the premises with new requirements in regard to the level of illumination
- sturdy, extremely reliable high-quality light fitting for application in unprotected outdoor areas
- high impact resistant housing, chemical and UV resistant
- PMMA diffuser with high mechanical and UV-resistance
- UV, ozone, weather, chemical and ageing resistant profile gasket
- pressure compensation system to prevent condensation inside the light fitting
- sturdy safety clips to ensure protection against accidental contact
- FastFix mounting system with stainless steel mounting clips for variable mounting distances
- front-side in/out wiring possible as standard
- variable cable entry possible through additional entries on the top of the enclosure at the front or in the centre, centring holes available
- homogenous illumination due to frosted diffuser, comfortable perception of light
- maximum standardisation and highly economical storage (only one light fitting instead of multiple versions)
- sustainable, interchangeable components
- future proof by using standardised Zhaga LED modules



Applications

- humid, wet and dusty indoor areas and sheltered outdoor areas in commerce, trade and industry etc.
- unprotected outdoor areas, e.g. mounted to industrial plants, external gangways, stairs, walls, ceilings, doors, bus stops, train stations, subways, construction sites, under canopies etc. The light is not to be used in areas with high mechanical stress (wind) or seldom usage (i.e. maintenance and inspection only, please use light fittings from the 144..AUS or PRIMO XR series)
- areas, where one standardised LED-light fitting with variable setting of luminous flux shall be used for different illumination tasks

PROXIMA
161PX 15L VARIO AUS
[Item no. : 16131 0091]

Technical data

General

EAN/GTIN:	4041254393360

Key technical data

Light source:	LED
LED module standard:	Zhaga
Exchangeability:	light source and control gear replaceable by qualified person
Connected load:	12 W, 49 W
Luminaire luminous flux:	1980 lm, 7410 lm
Luminous efficacy:	165 lm/W, 151 lm/W
Colour temperature:	4000 K
Colour rendering (CRI):	≥ 80
Light colour:	840
Admissible ambient temperature T_a:	-20 °C to +50 °C
Control gear:	1 x ECG, Overload protection, Short circuit protection
Energy efficiency class:	B
I LED max:	400 mA
BEG-eligible (Germany):	Yes
Special features:	variable and almost stepless adjustable luminous flux/connected load (Attention: only min, max values listed above). Max. ambient temperature depending on luminous flux setting

Lighting technology

Light distribution:	symmetrical wide beam
Beam angle:	120 °
Photobiological safety:	RG1

Service life

Service life LED:	L90>50000 h (@ Ta 25°C), L80>70000 h (@ Ta max), L70>100000 h (@ Ta max)

Electrical connection

Rated voltage:	220 - 240 V, 50/60 Hz
Terminal clamp:	Cage clamp, 3-polig, 0,75 - 2,5 mm²
Max. no. with circuit breaker B16:	16
CB B10/B13/B20:	11/13/21
CB C10/C13/C16/C20:	16/21/27/33

Electrical connection

Cable entries:	M20 (3x), pressure compensation element (1x), cable gland (2x), screw plug (1x), Plastic, 6 - 13 mm
In-out wiring (RR):	Yes

Features/Certificates

Protection class:	I
IP rating:	IP65
IK rating:	IK06
Limited surface temperature D:	Yes
Approval marks:	CE

Mounting

Mounting method (accessories possibly needed):	Ceiling, Ceiling with bracket, Ceiling with angle, Pole with pipe clamp, Pipe clamp, Wall, Wall with bracket, Wall with angle
Operating position:	downwards radiation, forwards radiation, horizontal
Mounting:	fast mounting system FastFix, 2-point

Housing

Housing material:	Glass fibre reinforced polyester
Colour:	grey

Cover

Cover type / material:	Diffuser (PMMA)
Cover characteristic:	satined
Closure:	Clips (Plastic)

Other features

Pressure compensation system:	Yes

Dimension/Weight

Length:	1578.00 mm
Width / Diameter:	137.00 mm
Height:	115.00 mm
Net weight:	3.57 kg

PROXIMA
161PX 15L VARIO AUS
[Item no. : 16131 0091]

Optional accessories / spare parts

Item no.	Item name	Item description
16111 9040	ABD 161PX 06	cover PMMA satined
16111 9041	ABD 161PX 12	cover PMMA satined
16111 9042	ABD 161PX 15	cover PMMA satined
16111 9043	ABD 161PX 06 PC	cover PC satined
16111 9044	ABD 161PX 12 PC	cover PC satined
16111 9045	ABD 161PX 15 PC	cover PC satined
16111 9046	ABD 161PX 06 LM	cover high chemical resistant clear IFS
16111 9047	ABD 161PX 12 LM	cover high chemical resistant clear IFS
16111 9048	ABD 161PX 15 LM	cover high chemical resistant clear IFS
90053 9009	KKS FR VE10	safety clips (10 pcs.)
90055 9007	KE/KES G2 VE10	locking clips (10 pcs.) with 2 safety clips
90053 9004	KKS FR P	safety clips (1 pair)
90055 9006	KES G2 P	safety clips (1 pair)
90063 9000	2511	blanking plug M20
25610 9000	2561	cable gland M20
25600 9000	2560	cable gland M25
90259 9002	DAE20	breather M20
90259 9003	DAE20/25	breather M20 with extension M25
90094 0005	183 RO 112 A P SD	
90094 0006	183 RO 2 A P SD	
90303 9000	SWABF 161PX E4 P	wall and ceiling mounting (1 pair) stainless steel 1.4571 swivel arm mounting
90295 9000	FB SENSOTEC-MINI	IR remote control