Damp-proof light fitting (LED-Retrofit)


164 2/15 RLED OV

[Item no. : 16415 0209]




General product description

Damp-proof light fitting for LED retrofit lamps. Glass fibre reinforced polyester housing, clear diffuser and clips. Reflector with sockets and terminal clamp and fuse, without ballast. See „Technical data“ for details. Note: Not suitable for retrofit lamps that are designed for use in ECG luminaires. Operate IEC 62776 certified lamps only that are released by the manufacturer to operate at mains voltage.



Zusätzliche Kabeleinführungen rückseitig (mit Presshaut)
Additional entries (knock-outs)



General product benefits

- high-quality light fitting with highly mechanical resistance
- Built-in clamp to switch off the retrofit lamp in the event of a fault
- variable cable entries

Applications

- humid, wet and dusty indoor areas and sheltered outdoor areas in commerce, trade and industry etc.
- for damp and cold ambient conditions with low duty cycles, please contact us

164 2/15 RLED OV

[Item no. : 16415 0209]

Technical data

General

EAN/GTIN:	4041254303628

Key technical data

Exchangeability:	light source replaceable by qualified person
Luminous efficacy:	0 lm/W
Admissible ambient temperature T_a:	-20 °C to +30 °C
Control gear:	Overload protection, Short circuit protection

Electrical connection

Rated voltage:	220 - 240 V, 50/60 Hz
Terminal clamp:	Screw terminal, 3-polig, 0,75 - 2,5 mm²
Cable entries:	M20 (2x), blanking plug (2x), Plastic, 8 - 15 mm

Features/Certificates

Protection class:	I
IP rating:	IP65
IK rating:	IK04
Approval marks:	CE

Mounting

Mounting method (accessories possibly needed):	Ceiling, Wall, Ceiling with bracket, Ceiling with angle, Suspended, Mounting rail, Wall with bracket, Wall with angle
Operating position:	downwards radiation, forwards radiation, horizontal
Mounting:	2-point

Housing

Housing material:	Glass fibre reinforced polyester
Colour:	grey

Cover

Cover type / material:	Diffuser (PMMA)
Cover characteristic:	pearled
Closure:	Clips (Plastic)

Dimension/Weight

Length:	1572.00 mm
Width / Diameter:	200.00 mm
Height:	98.00 mm
Net weight:	3.51 kg

164 2/15 RLED OV

[Item no. : 16415 0209]

Optional accessories / spare parts

Item no.	Item name	
16411 9001	164036	
16411 9002	164058	
16411 9004	ABD 164 036 PC	cover PC clear pearled
16411 9005	ABD 164 058 PC	cover PC clear pearled
90124 9003	164/1/30	
90063 9000	2511	blanking plug M20
25610 9000	2561	cable gland M20
25600 9000	2560	cable gland M25
90123 9003	163 KK VE08	locking clips (8 pcs.)
90123 9002	163 KE VE08	locking clips (8 pcs.)
90245 0005	164 RO 112 A P	2 pipe clamps 1 1/2", stainless steel, with support
90245 0006	164 RO 2 A P	2 pipe clamps 2", stainless steel, with support
90049 0002	183 S	hook stainless steel for chain mounting
90095 0001	DS 183	ceiling rail stainless steel with M5 screw
90294 9001	SI T 1,6A	