
LED high-bay floodlight

# DUEVO XL
# 3305 L440TB
**[ Item no. : 33050 0059 ]**




### General product description

LED high bay light fitting DUEVO XL of the GreenLine series with outstanding sustainable product design. Die-cast aluminium housing, powder-coated, multi-part, thermally separated, consisting of: Two ECG housings with incorporated ECG and smooth surface, ready for connection as well as four LED housings with LED modules, highly efficient optics, frameless tempered safety glass pane and surface with flat cooling fins. LED modules, direct beam, Multi-Layer Technology, with direct connection to the housing for perfect thermal management. ECG with overload and short circuit protection. See "Optional accessories" for mounting material.




### General product benefits

- extremely high service life due to high-quality components and optimal thermal management
- perfect thermal management due to direct connection of the LED modules to the housing and separation of ECG and LED housing, large cooling surface, excellent thermal conductivity
- uniform illumination due to Multi-Layer Technology, i.e. every individual LED illuminates the whole surface, the light distribution curves of the LED are overlapping
- "D"-sign - suitable for rooms with increased risk of fire
- colour rendering index CRI>80, according to the workplace guidelines suitable for nearly all plant locations
- variable electrical connection options due to 8 cable entries on the top and side (optional in-out wiring)
- sustainable, interchangeable components
- future proof by using standardised Zhaga LED modules
- GreenLine luminaire, outstanding sustainable design




### Applications

- production areas and warehouses in commerce, trade and industry with high mounting heights or with requirement for high illumination levels, e.g. shipyards, hangars, machine-, maintenance- and assembly shops for large-scale equipment and heavy industry, maintenance halls, assembly plants, cold Rooms, refrigerated warehouses, DIY stores, rack aisles, high-bay warehouses

# DUEVO XL
# 3305 L440TB
## [ Item no. : 33050 0059 ]

### Technical data

**General**

| | |
|---|---|
| EAN/GTIN: | 4041254315706 |

**Key technical data**

| | |
|---|---|
| Light source: | LED |
| LED module standard: | Zhaga |
| Exchangeability: | light source and control gear replaceable by qualified person |
| Connected load: | 268 W |
| Luminaire luminous flux: | 43200 lm |
| Luminous efficacy: | 161 lm/W |
| Colour temperature: | 4000 K |
| Colour rendering (CRI): | ≥ 80 |
| Light colour: | 840 |
| Admissible ambient temperature $T_a$: | -25 °C to +60 °C |
| Control gear: | 4 x ECG, Overload protection, Short circuit protection |
| Energy efficiency class: | C |
| Overvoltage protection: | 4 kV |
| I LED max: | 350 mA |
| BEG-eligible (Germany): | Yes |

**Lighting technology**

| | |
|---|---|
| Optical system: | Lens optics |
| Optical system material: | PMMA |
| Light distribution: | narrow wide beam |
| Beam angle: | 65 ° |
| Photobiological safety: | RG1 |

**Service life**

| | |
|---|---|
| Service life LED: | L70>100000 h (@ Ta max), L90>50000 h (@ Ta 25°C) |

**Electrical connection**

| | |
|---|---|
| Rated voltage: | 220 - 240 V, 50/60 Hz |
| Terminal clamp: | Cage clamp, 3-polig, 0,75 - 2,5 mm² |
| Max. no. with circuit breaker B16: | 3 |
| CB B10/B13/B20: | 2/3/4 |
| CB C10/C13/C16/C20: | 3/4/5/6 |
| Cable entries: | M25 (2x), cable gland (1x), screw plug (1x) |

**Features/Certificates**

| | |
|---|---|
| Protection class: | I |
| IP rating: | IP65 |
| IK rating: | IK10 |
| Limited surface temperature D: | Yes |
| Approval marks: | CE |

**Mounting**

| | |
|---|---|
| Mounting method (accessories possibly needed): | Suspended |
| Operating position: | downwards radiation |
| Mounting: | Multi-point |

**Housing**

| | |
|---|---|
| Housing material: | Die-cast aluminium |
| Varnished: | Yes |
| Colour: | grey, DB 702 |

**Cover**

| | |
|---|---|
| Cover type / material: | Pane (Safety glass) |
| Cover characteristic: | clear |
| Closure: | screwed (Stainless steel (1.4301)) |

**Sustainability**

| | |
|---|---|
| GreenLine: | Yes |
| Rezyklat material content ≥ 50%: | 60 % |
| Dismountable at end of life: | Yes |
| ≥ 80% recycelable: | 80 % |
| Construction modular: | Yes |
| Spareparts availability > 10 years: | Yes |
| luminaire is upgradeable: | Yes |
| Guarantee 5 years: | Yes |
| Packaging made of 100% recyclet paper: | Yes |

**Dimension/Weight**

| | |
|---|---|
| Length: | 877.00 mm |
| Width / Diameter: | 850.00 mm |
| Height: | 101.00 mm |
| Net weight: | 30.30 kg |

# DUEVO XL
# 3305 L440TB
**[ Item no. : 33050 0059 ]**

**Optional accessories / spare parts**

| Item no. | Item name | Item description |
|---|---|---|
| 33001 9001 | ABD 3301 ESGW | safety glass pane clear (for 1 segment) |
| 33001 9010 | ABD 3301 C PMMA | PMMA pane frosted for glare limitation (for 1 segment) |
| 25600 9000 | 2560 | cable gland M25 |
| 25720 9000 | 2572 | screw plug M25 |
| 90022 0007 | BF SAH Y 420/90 ST P | 1 pair of Y-ropes |