
LED high-bay floodlight


TRIANO disc
3410 L100 IFS
[Item no. : 34100 0005]



General product description


LED high bay luminaire TRIANO disc. Robust die-cast aluminum body with cooling fin structure and integrated ECG housing, powder-coated, built-in control gear, quick-connect plug, eyebolt for 1-point mounting, LED module as well as PC cover. LED module, Multi-Layer technology, with direct connection to the housing for perfect thermal management. Electronic ballast with overload and short-circuit protection, electrical connection via quick connector (FastConnect), male connector pre-installed, female attached.





General product benefits

- for application in food industry areas, in accordance with IFS/BRC/VDMA standards, applicable without restrictions in plants, that have to fulfil the HACCP Concept
- fast and easy mounting and connection due to 1-point mounting and plug connection (FastConnect)
- perfect thermal management due to cooling fin structure and direct connection of the LED module to the housing, large cooling surface, excellent thermal conductivity
- extremely high service life due to high-quality components and optimal thermal management
- colour rendering index CRI>80, according to the workplace guidelines suitable for nearly all plant locations
- "D"-sign - suitable for rooms with increased risk of fire
- uniform illumination due to Multi-Layer Technology, i.e. every individual LED illuminates the whole surface, the light distribution curves of the LED are overlapping
- sustainable, interchangeable components



Applications

- production areas and warehouses in commerce, trade and industry, maintenance halls, assembly plants, cold Rooms, refrigerated warehouses, DIY stores, rack aisles, high-bay warehouses
- production areas and warehouses in the food industry and food processing areas as well as suppliers to the food industry, that have to meet the requirements of the International Food Standard, BRC, HACCP or comparably strict requirements, e.g. food packaging production areas

TRIANO disc
3410 L100 IFS
[Item no. : 34100 0005]

Technical data

General
EAN/GTIN: 4041254350547

Key technical data
Light source: LED
Exchangeability: light source and control gear replaceable by qualified person
Connected load: 65 W
Luminaire luminous flux: 9400 lm
Luminous efficacy: 145 lm/W
Colour temperature: 5000 K
Colour rendering (CRI): ≥ 80
Light colour: 850
Admissible ambient temperature T_a: -25 °C to +50 °C
Control gear: 1 x ECG, Overload protection, Short circuit protection
Energy efficiency class: C
Overvoltage protection: 4 kV
I LED max: 350 mA
BEG-eligible (Germany): Yes

Lighting technology
Light distribution: wide beam
Beam angle: 120 °
Photobiological safety: RG0

Service life
Service life LED: L70>100000 h (@ Ta max), L90>50000 h (@ Ta 25°C)

Electrical connection
Rated voltage: 220 - 240 V, 50/60 Hz
Terminal clamp: Plug, Screw terminal, 3-polig, 0,75 - 2,5 mm²
Max. no. with circuit breaker B16: 15
CB B10/B13/B20: 10/13/19
CB C10/C13/C16/C20: 15/20/25/31
Cable entries: cable gland (1x), Plastic, 6 - 10 mm

Features/Certificates
Protection class: I
IP rating: IP65
IK rating: IK09
Limited surface temperature D: Yes
Approval marks: CE

Mounting
Mounting method (accessories possibly needed): Suspended

Mounting
Operating position: downwards radiation
Mounting: 1-point

Housing
Housing material: Die-cast aluminium
Varnished: Yes
Colour: grey, DB 702

Cover
Cover type / material: Pane (PC)
Cover characteristic: clear
Closure: screwed (Stainless steel (1.4301))

Other features
International Food Standard (IFS): Yes

Dimension/Weight
Width / Diameter: 312.00 mm
Height: 146.00 mm
Net weight: 2.10 kg

TRIANO disc
3410 L100 IFS
[Item no. : 34100 0005]

Optional accessories / spare parts

Item no.	Item name	Item description
34011 9001	ABD TRIANO ESGW	spare safety glass (for 1 segment)
34011 9003	ABD TRIANO PRA PMMA	spare cover PMMA with prismatic structure (for 1 segment)
34011 9002	ABD TRIANO PC	PC cover for food industry/IFS version (for 1 segment)
34011 9004	ABD TRIANO B PC	spare cover PC with wide beam optics (for 1 segment)
34011 9005	ABD TRIANO TB PC	spare cover PC with narrow wide beam optics (for 1 segment)
34011 9006	ABD TRIANO T PC	spare cover PC with narrow beam optics (for 1 segment)
90547 9001	LACA FM FC	LIMAS Air CASA wireless module FastConnect
90547 9003	LACA FM OP FC	LIMAS Air CASA wireless module FastConnect with surge protection 10 kV
90547 9004	LACA FM OP FC MK1	LIMAS Air CASA wireless module FastConnect with surge protection 10 kV and 1 m cable
90547 9002	LACA FM FC MK1	LIMAS Air CASA wireless module FastConnect with 1 m cable