
LED high-bay floodlight

TRIANO disc
3410 L100B G4 DIMD T40
[Item no. : 34102 0005]




General product description


LED high bay luminaire TRIANO disc. Robust die-cast aluminum body with cooling fin structure and integrated ECG housing, powder-coated, built-in control gear, eyebolt for 1-point mounting, LED module as well as PC covers with integrated optics. LED module, with direct connection to the housing for perfect thermal management, thermal switch. NFC-enabled electronic ballast with overload and short-circuit protection, electrical connection via quick connector (FastConnect).



General product benefits

- for application in food industry areas, in accordance with IFS/BRC/VDMA standards, applicable without restrictions in plants, that have to fulfil the HACCP Concept
- fast and easy mounting and connection due to 1-point mounting and plug connection (FastConnect)
- perfect thermal management due to cooling fin structure and direct connection of the LED module to the housing, large cooling surface, excellent thermal conductivity
- extremely high service life due to high-quality components and optimal thermal management
- colour rendering index CRI>80, according to the workplace guidelines suitable for nearly all plant locations
- "D"-sign - suitable for rooms with increased risk of fire
- interchangeable components





Applications

- production areas and warehouses in commerce, trade and industry, maintenance halls, assembly plants, cold Rooms, refrigerated warehouses, DIY stores, rack aisles, high-bay warehouses
- production areas and warehouses in the food industry and food processing areas as well as suppliers to the food industry, that have to meet the requirements of the International Food Standard, BRC, HACCP or comparably strict requirements, e.g. food packaging production areas

TRIANO disc
3410 L100B G4 DIMD T40
[Item no. : 34102 0005]

Technical data

General

EAN/GTIN:	4041254453897

Key technical data

Light source:	LED
Exchangeability:	light source and control gear replaceable by qualified person
Connected load:	56 W
Luminaire luminous flux:	10000 lm
Luminous efficacy:	179 lm/W
Colour temperature:	4000 K
Colour rendering (CRI):	≥ 80
Light colour:	840
Admissible ambient temperature T_a:	-40 °C to +60 °C
Control gear:	1 x ECG (NFC-enabled), Overload protection, Short circuit protection
Energy efficiency class:	B
Overvoltage protection:	2 kV
I LED max:	425 mA

Lighting control

Dimmable:	Yes
Dimming method:	DALI (DIMD)
Dimming range:	10 - 100 %

Lighting technology

Optical system:	Lens optics with prismatic structure
Optical system material:	PC
Light distribution:	wide beam
Beam angle:	80 °
Photobiological safety:	RG1

Service life

Service life LED:	L95>100000 h (@ Ta max)

Electrical connection

Rated voltage:	220 - 240 V, 50/60 Hz
Terminal clamp:	Plug, Cage clamp, 5-polig, 0,5 - 2,5 mm²
Max. no. with circuit breaker B16:	46
CB B10/B13/B20:	29/38/58
CB C10/C13/C16/C20:	47/62/78/95
Cable entries:	cable gland (1x), Plastic, 9 - 17 mm

Features/Certificates

Protection class:	I
IP rating:	IP65
IK rating:	IK09
Limited surface temperature D:	Yes

Features/Certificates

Approval marks:	CE

Mounting

Mounting method (accessories possibly needed):	Suspended
Operating position:	downwards radiation
Mounting:	1-point

Housing

Housing material:	Die-cast aluminium
Varnished:	Yes
Colour:	grey, DB 702

Cover

Cover type / material:	Optics (PC)
Cover characteristic:	clear with outer-prisms
Closure:	screwed

Other features

International Food Standard (IFS):	Yes

Product life cycle

Guarantee 5 years:	Yes

Dimension/Weight

Width / Diameter:	312.00 mm
Height:	135.00 mm
Net weight:	2.10 kg

TRIANO disc
3410 L100B G4 DIMD T40
[Item no. : 34102 0005]

Optional accessories / spare parts

Item no.	Item name	Item description
34011 9004	ABD TRIANO B PC	PC pane clear, wide beam optics, (for 1 segment)
34011 9005	ABD TRIANO TB PC	PC pane clear, narrow wide beam, (for 1 segment)