
LED outdoor light fitting

VIA
52 4802 730
[Item no. : 52000 0017]




General product description

LED outdoor light fitting VIA consisting of powder-coated die-cast aluminum housing, hinged, with safety clip. LED module(s) and ECG mounted on tool-free removable support plates in the upper part of the housing. Cable entry with gland and strain relief, disconnect plug connection and pressure equalization system in the lower part of the housing, flat safety glass, silicone seal, central locking made of aluminum. Zhaga compliant LED modules with high efficiency optics, direct beam, multi-layer technology. ECG with high surge voltage resistance, overload and short circuit protection. Universal mast spigot made of die-cast aluminum for mast spigot 60/76 for mast mounting or mast mounting. Separate reducing accessories are required for mast spigot 42. Tilt adjustment 0°, 5°, 10°, 15° for surface mounting, 0°, -5°, -10°, -15° for surface mounting, scaling on luminaire housing.



General product benefits

- long-lasting, corrosion-resistant die-cast aluminium housing with smooth surface without cooling fins
- quick and easy mounting due to toolless opening of the light fitting by means of a central toggle clamp lever
- no uncomfortable "working overhead", light fitting opens upwards
- pre-assembled universal pole attachment for pole spigot 60 and 76 for pole attachment or pole top mounting
- easy insertion of the cable into the terminal compartment due to cable gland
- tool-free exchange of the LED board (carrier plate, disconnect plug, clamping spring) as well as ECG exchange (carrier plate, disconnect plug, clamping spring)
- time- and cost-saving component replacement at the end of service life or retrofitting in the event of further technical development or the use of other / warmest light colours
- homogenous illumination due to Multi-Layer Technology
- integrated pressure compensation system prevents condensation inside the light fitting
- no light emission into the upper half space, ULOR=0
- versions dimmable to 10% and with color temperature up to 3,000 K comply with Dark Sky requirements
- components tool-free interchangeable
- future proof by using standardised Zhaga LED modules



Applications

- residential streets, main and by-roads, roundabouts, walkways and cycle lanes, traffic-calmed zones, streets on factory sites, parking areas, car parks, gateways etc.

LED outdoor light fitting

VIA
52 4802 730
[Item no. : 52000 0017]

Technical data

General

EAN/GTIN:	4041254381466

Key technical data

Light source:	LED
LED module standard:	Zhaga
Exchangeability:	light source and control gear replaceable by qualified person
Connected load:	75 W
Luminaire luminous flux:	11920 lm
Luminous efficacy:	159 lm/W
Colour temperature:	3000 K
Colour rendering (CRI):	≥ 70
Light colour:	730
Admissible ambient temperature T_a:	-40 °C to +40 °C
Control gear:	1 x ECG (NFC-enabled), Overload protection, Short circuit protection
Energy efficiency class:	C
Overvoltage protection:	10 kV
I LED max:	500 mA

Lighting technology

Optical system:	Lens optics
Optical system material:	PMMA
Light distribution:	asymmetrical wide beam
Photobiological safety:	RG1

Service life

Service life LED:	L95>100000 h (@ Ta max)

Electrical connection

Rated voltage:	220 - 240 V, 50/60 Hz
Terminal clamp:	Plug, Screw terminal, 3-polig, 0,75 - 2,5 mm²
Max. no. with circuit breaker B16:	23
CB B10/B13/B20:	15/19/29
CB C10/C13/C16/C20:	23/31/39/47
Cable entries:	blanking plug (1x), Plastic, 9 - 14 mm

Features/Certificates

Protection class:	II
IP rating:	IP66
IK rating:	IK09
Approval marks:	CE

Mounting

Mounting method (accessories possibly needed):	Side-entry mounting, Pole-top mounting
Operating position:	downwards radiation
Side-entry mounting:	Ø 60mm x 100mm, Ø 76mm x 90mm
Pole-top mounting:	Ø 60/76mm

Mounting

Inclination side-entry:	0 °, -5 °, -10 °, -15 °
Inclination pole-top:	0 °, 5 °, 10 °, 15 °
Wind-exposed surface:	0.21 m²

Housing

Housing material:	Die-cast aluminium
Varnished:	Yes
Colour:	grey, DB 702

Cover

Cover type / material:	Pane (Safety glass)
Cover characteristic:	clear
Closure:	screwed

Other features

Pressure compensation system:	Yes

Product life cycle

Dismountable at end of life:	Yes
recyclable:	80 %
Construction modular:	Yes
Spareparts availability > 10 years:	Yes
luminaire is upgradeable:	Yes
Guarantee 5 years:	Yes
Packaging made of 95% recyclet paper:	Yes

Dimension/Weight

Length:	693.00 mm
Width / Diameter:	368.00 mm
Height:	222.00 mm
Net weight:	10.70 kg

VIA
52 4802 730
[Item no. : 52000 0017]

Optional accessories / spare parts

Item no.	Item name	Item description
52010 9000	ABD 52 ESGW	safety glass pane clear
90113 0002	HA 08/L25	Shielding on the house side , plastic (PC) for item name 08... and L25...
90113 0003	HA 16/L50	Shielding on the house side , plastic (PC) for item name 16... and L50...
90113 0004	HA 24/L75	Shielding on the house side , plastic (PC) for item name 24... and L75...
90113 0005	HA 32/L100	Shielding on the house side , plastic (PC) for item name 32... and L100...
90309 0001	RZ 76/42 VIA	