
LED rope-supported light fitting

REDONDO
55 6402 FC
[Item no. : 55000 0011]




General product description

LED rope-supported light fitting REDONDO consisting of powder-coated die-cast aluminium housing, with bracket, adjustable inclination, plug connection system (FastConnect) and pressure compensation system. LED module(s) and ECG mounted on tool-free removable support plates in the housing and connected with isolating plug connection. Frameless flat safety glass can be opened without tools using an integrated toggle clamp lever. The terminal box and all electronic components are accessible by opening the PC cover. Zhaga LED modules with highly efficient optics, direct beam, Multi-Layer Technology. ECG with high surge protection, overload and short circuit protection. Rope mounting with stainless steel bracket, rotatable (360°) and tiltable (15°) for ropes Ø 6-12mm.



General product benefits

- long-lasting, corrosion-resistant die-cast aluminium housing with smooth surface without cooling fins
- Integrated pressure equalisation system for defined ‘breathing’ prevents condensation from forming inside the luminaire.
- tool-free exchange of the LED board (carrier plate, disconnect plug, clamping spring) as well as ECG exchange (carrier plate, disconnect plug, clamping spring)
- universal usage on crosswise, lengthwise and inclined ropes or 3-point rope supports (see "Optional accessories")
- homogenous illumination due to Multi-Layer Technology, i.e. every individual LED illuminates the whole surface, the light distribution curves of the LED are overlapping
- no light emission into the upper half space, ULOR=0
- versions dimmable to 10% and with color temperature up to 3,000 K comply with Dark Sky requirements
- interchangeable components
- future proof by using standardised Zhaga LED modules



Applications

- Residential streets, main and by-roads with rope mounting

LED rope-supported light fitting

REDONDO
55 6402 FC
[Item no. : 55000 0011]

Technical data

General

EAN/GTIN:	4041254421902

Key technical data

Light source:	LED
LED module standard:	Zhaga
Exchangeability:	light source and control gear replaceable by qualified person
Connected load:	99 W
Luminaire luminous flux:	17520 lm
Luminous efficacy:	177 lm/W
Colour temperature:	4000 K
Colour rendering (CRI):	≥ 70
Light colour:	740
Admissible ambient temperature T_a:	-40 °C to +40 °C
Control gear:	1 x ECG (NFC-enabled), Overload protection, Short circuit protection
Energy efficiency class:	B
Overvoltage protection:	10 kV
I LED max:	500 mA

Lighting technology

Optical system:	Lens optics
Optical system material:	PMMA
Light distribution:	symmetrical wide beam
Photobiological safety:	RG1

Service life

Service life LED:	L95>100000 h (@ Ta max)

Electrical connection

Rated voltage:	220 - 240 V, 50/60 Hz
Terminal clamp:	Plug, Screw terminal, 3-polig, 0,75 - 2,5 mm²
Max. no. with circuit breaker B16:	7
CB B10/B13/B20:	5/6/9
CB C10/C13/C16/C20:	7/9/11/14
Cable entries:	M20 (1x), cable gland (1x), Plastic, 6 - 10 mm
Special features:	FastConnect - quick connection without opening the light fitting

Features/Certificates

Protection class:	II
IP rating:	IP66
IK rating:	IK09
Approval marks:	CE

Mounting

Mounting method (accessories possibly needed):	Rope

Mounting

Operating position:	downwards radiation
Swivel range:	-15 - 15 °
Rope diameter:	6 - 12 mm
Wind-exposed surface:	0.05 m²

Housing

Housing material:	Die-cast aluminium
Varnished:	Yes
Colour:	grey, DB 702

Cover

Cover type / material:	Pane (Safety glass)
Cover characteristic:	clear
Closure:	screwed (Stainless steel V4A)

Other features

Pressure compensation system:	Yes
Special features:	FastConnect (FC)

Product life cycle

Dismountable at end of life:	Yes
recyclable:	80 %
Construction modular:	Yes
Spareparts availability > 10 years:	Yes
luminaire is upgradeable:	Yes
Guarantee 5 years:	Yes
Packaging made of 95% recyclet paper:	Yes

Dimension/Weight

Width / Diameter:	488.00 mm
Height:	207.00 mm
Net weight:	7.50 kg

REDONDO
55 6402 FC
[Item no. : 55000 0011]

Optional accessories / spare parts

Item no.	Item name	Item description
55010 0001	ABD 55 ESGW	safety glass pane clear
90113 0026	HA 16/L50 WH SCR	Shielding on the house side, plastic (PC), white with screw fastening, for item name 16... and L50...
90113 0028	HA 32/L100 WH SCR	Shielding on the house side, plastic (PC), white with screw fastening, for item name 32... and L100...
90113 0029	HA 48/L150 WH SCR	Shielding on the house side, plastic (PC), white with screw fastening, for item name 48... and L150...
90113 0030	HA 64/L210 WH SCR	Shielding on the house side, plastic (PC), white with screw fastening, for item name 64... and L210...
90549 0001	ESSB HSM	Inrush current limiter for top-hat rail mounting
99100 0040	AKB 4,0m H07RN-F 3G1,5	Connection cable 4,0 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
99100 0041	AKB 4,5m H07RN-F 3G1,5	Connection cable 4,5 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
99100 0042	AKB 5,0m H07RN-F 3G1,5	Connection cable 5,0 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
99100 0044	AKB 6,0m H07RN-F 3G1,5	Connection cable 6,0 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
99100 0046	AKB 7,0m H07RN-F 3G1,5	Connection cable 7,0 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
99100 0048	AKB 8,0m H07RN-F 3G1,5	Connection cable 8,0 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
99100 0050	AKB 9,0m H07RN-F 3G1,5	Connection cable 9,0 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
99100 0052	AKB 10,0m H07RN-F 3G1,5	Connection cable 10,0 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
99100 0056	AKB 12,0m H07RN-F 3G1,5	Connection cable 12,0 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
99100 0074	AKB 5,0m H07RN-F 4G1,5	Connection cable 5,0 m H07RN-F 4x1,5mm², connected to the above mentioned luminaire
99100 0076	AKB 6,0m H07RN-F 4G1,5	Connection cable 6,0 m H07RN-F 4x1,5mm², connected to the above mentioned luminaire
99100 0078	AKB 7,0m H07RN-F 4G1,5	Connection cable 7,0 m H07RN-F 4x1,5mm², connected to the above mentioned luminaire
99100 0080	AKB 8,0m H07RN-F 4G1,5	Connection cable 8,0 m H07RN-F 4x1,5mm², connected to the above mentioned luminaire

REDONDO
55 6402 FC
[Item no. : 55000 0011]

99100 0082	AKB 9,0m H07RN-F 4G1,5	Connection cable 9,0 m H07RN-F 4x1,5mm², connected to the above mentioned luminaire
99100 0084	AKB 10,0m H07RN-F 4G1,5	Connection cable 10,0 m H07RN-F 4x1,5mm², connected to the above mentioned luminaire
99100 0088	AKB 12,0m H07RN-F 4G1,5	Connection cable 12,0 m H07RN-F 4x1,5mm², connected to the above mentioned luminaire