

LED pole-top light fitting

CILA
558 0803R G2 730
[Item no. : 55801 0021]







General product description

LED pole-top light fitting CILA, consisting of powder-coated aluminium pole mount and roof as well as clear cylindrical PMMA cover. LED module and ECG unit wired ready for connection, disconnect plug connection to mains terminal and strain relief for connection cable. Zhaga LED modules with highly efficient optics and frosted cover, direct beam, Multi-Layer Technology. ECG with high surge protection, overload and short circuit protection. Mounting on straight poles Ø 76mm (see "Optional accessories" for poles Ø 60mm).

General product benefits

- optimal light distribution due to highly efficient lens optics with direct beam
- uniform illumination due to Multi-Layer-Technology, i.e. every individual LED illuminates the whole surface, the light distribution curves of the LED are overlapping
- quick installation, maintenance and conversion thanks to tool-free opening of the light fitting and tool-free replacement of the electrical components (LED module and ECG unit)
- BlackEdition, ULOR=0% (Modifications with accessories influence the light distribution)
- versions dimmable to 10% with luminous fluxes up to 2000 lm and with color temperature up to 3,000 K comply with Dark Sky requirements
- components tool-free interchangeable
- future proof by using standardised Zhaga LED modules

Applications

- promenades, public parks, pedestrian areas, public places etc.

BLACK EDITION

LED pole-top light fitting

CILA
558 0803R G2 730
[Item no. : 55801 0021]

Technical data

General

EAN/GTIN:	4041254395227

Key technical data

Light source:	LED
LED module standard:	Zhaga
Exchangeability:	light source and control gear replaceable by qualified person
Connected load:	18 W
Luminaire luminous flux:	2560 lm
Luminous efficacy:	142 lm/W
Colour temperature:	3000 K
Colour rendering (CRI):	≥ 70
Light colour:	730
Admissible ambient temperature T_a:	-40 °C to +35 °C
Control gear:	1 x ECG (NFC-enabled), Overload protection, Short circuit protection
Energy efficiency class:	C
Overvoltage protection:	10 kV
I LED max:	700 mA

Lighting technology

Optical system:	Lens optics
Optical system material:	PMMA
Light distribution:	rotationally symmetrical beam
Photobiological safety:	RG1
Light emission:	ULOR=0%

Service life

Service life LED:	L95>100000 h (@ Ta max)

Electrical connection

Rated voltage:	220 - 240 V, 50/60 Hz
Terminal clamp:	Plug, Screw terminal, 3-polig, 0,75 - 2,5 mm²
Max. no. with circuit breaker B16:	23
CB B10/B13/B20:	15/19/29
CB C10/C13/C16/C20:	23/31/39/47
Cable entries:	0 - 16 mm

Features/Certificates

Protection class:	II
IP rating:	IP54
IK rating:	IK06
Approval marks:	CE

Mounting

Mounting method (accessories possibly needed):	Pole-top mounting
Operating position:	downwards radiation
Pole-top mounting:	Ø 76mm
Wind-exposed surface:	0.13 m²

Housing

Housing material:	Aluminium
Varnished:	Yes
Colour:	grey, DB 702

Cover

Cover type / material:	Cylinder (PMMA)
Cover characteristic:	clear
Protective cover:	Roof (aluminium)

Other features

Pressure compensation system:	Yes
Special features:	ULOR=0%

Dimension/Weight

Width / Diameter:	206.00 mm
Height:	561.00 mm
Net weight:	4.70 kg

CILA
558 0803R G2 730
[Item no. : 55801 0021]

Optional accessories / spare parts

Item no.	Item name	Item description
10051 9000	ABD 541/55. G2 PMMA	spare cover PMMA clear
10041 9001	ABDP 54./55. C PMMA	cover for glare limitation
90113 0025	HA 08/L25 WH SCR	Shielding on the house side, plastic (PC), white with screw fastening, for item name 08... and L25...
90113 0032	HA 08/L25 WH BC	Shielding on the house side, plastic (PC), with mounting clip, for item name 08... and L25...
90113 0026	HA 16/L50 WH SCR	Shielding on the house side, plastic (PC), white with screw fastening, for item name 16... and L50...
90113 0033	HA 16/L50 WH BC	Shielding on the house side, plastic (PC), with mounting clip, for item name 16... and L50...
90549 0001	ESSB HSM	Inrush current limiter for top-hat rail mounting
90116 9004	RS 54./55. G2	ring mirror aluminium
90126 0001	RZ 1 BK	reducer ø76 -> 60mm
90044 0001	RZ 1 GY	reducer ø76 -> 60mm
62599 0001	MAU 625/1	pole-top bracket for 1 light fitting ø=60mm
62599 0002	MAU 625/2	pole-top bracket for 2 light fittings ø=60mm
62599 0003	MAU 625/3	pole-top bracket for 3 light fittings ø=60mm
62599 0004	MAU 625/4	pole-top bracket for 4 light fittings ø=60mm
99100 0040	AKB 4,0m H07RN-F 3G1,5	Connection cable 4,0 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
99100 0041	AKB 4,5m H07RN-F 3G1,5	Connection cable 4,5 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
99100 0042	AKB 5,0m H07RN-F 3G1,5	Connection cable 5,0 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
99100 0044	AKB 6,0m H07RN-F 3G1,5	Connection cable 6,0 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
99100 0046	AKB 7,0m H07RN-F 3G1,5	Connection cable 7,0 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
99100 0048	AKB 8,0m H07RN-F 3G1,5	Connection cable 8,0 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
99100 0050	AKB 9,0m H07RN-F 3G1,5	Connection cable 9,0 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
99100 0052	AKB 10,0m H07RN-F 3G1,5	Connection cable 10,0 m H07RN-F 3x1,5mm², connected to the above mentioned luminaire
		Connection cable 12,0 m H07RN-F 3x1,5mm², connected to the above

CILA
558 0803R G2 730
[Item no. : 55801 0021]

99100 0056	AKB 12,0m H07RN-F 3G1,5	mentioned luminaire
99100 0074	AKB 5,0m H07RN-F 4G1,5	Connection cable 5,0 m H07RN-F 4x1,5mm², connected to the above mentioned luminaire
99100 0076	AKB 6,0m H07RN-F 4G1,5	Connection cable 6,0 m H07RN-F 4x1,5mm², connected to the above mentioned luminaire
99100 0078	AKB 7,0m H07RN-F 4G1,5	Connection cable 7,0 m H07RN-F 4x1,5mm², connected to the above mentioned luminaire
99100 0080	AKB 8,0m H07RN-F 4G1,5	Connection cable 8,0 m H07RN-F 4x1,5mm², connected to the above mentioned luminaire
99100 0082	AKB 9,0m H07RN-F 4G1,5	Connection cable 9,0 m H07RN-F 4x1,5mm², connected to the above mentioned luminaire
99100 0084	AKB 10,0m H07RN-F 4G1,5	Connection cable 10,0 m H07RN-F 4x1,5mm², connected to the above mentioned luminaire
99100 0088	AKB 12,0m H07RN-F 4G1,5	Connection cable 12,0 m H07RN-F 4x1,5mm², connected to the above mentioned luminaire