
8118/6

[Item no. : 81180 0002]





8118/6

[Item no. : 81180 0002]

Technical data

General

EAN/GTIN:	4041254157207

Explosion protection

EX-Zone:	1 , 21 , 2 , 22
EX-marking gas:	II 2 G Ex eb IIC T6....T5 Gb
EX-marking dust:	II 2 D Ex tb IIIC T80°C....T95°C Db
Primary ignition protection method:	eb
Temperature class:	T6
ATEX:	PTB 99 ATEX 3103
IECEx:	IECEx PTB 06.0026

Key technical data

Luminous efficacy:	0 lm/W
Admissible ambient temperature T_a:	-40 °C to +40 °C
Control gear:	Overload protection, Short circuit protection
Special features:	Temperature class T5: -40°C up to +55°C

Electrical connection

Terminal clamp:	5-polig, - 6 mm²
Cable entries:	M25 (6x), cable gland (6x), Plastic, 7 - 17 mm
In-out wiring (RR):	Yes

Features/Certificates

Protection class:	I
IP rating:	IP66
Approval marks:	CE

Housing

Housing material:	Glass fibre reinforced polyester
Colour:	black

Dimension/Weight

Length:	180.00 mm
Width / Diameter:	180.00 mm
Height:	64.00 mm
Net weight:	0.61 kg