

Explosion-protected LED high-bay floodlight

ExDUEVO

nD8302 L320

[Item no. : 83020 0002]



General product description



Explosion-protected LED high bay light fitting ExDUEVO of the GreenLine series with outstanding sustainable product design for zone 2/22. Die-cast aluminium housing, multi-part, thermally separated, powder-coated, consisting of: ECG housing with incorporated ECG and smooth surface as well as two LED housings with LED modules, frameless tempered safety glass pane and surface with flat cooling fins. LED modules direct beam, Multi-Layer-Technology, with direct connection to the housing for perfect thermal management. ECG with overvoltage, overload and short circuit protection as well as DALI interface for dimming operation.

General product benefits

- extremely high service life even at maximum admissible ambient temperature
- perfect thermal management due to direct connection of the LED modules to the housing and separation of ECG and LED housing, large cooling surface, excellent thermal conductivity
- DALI interface (standard) for dimming operation
- colour rendering index $CRI \geq 80$, according to the workplace guidelines suitable for nearly all plant locations
- uniform illumination due to Multi-Layer-Technology, i.e. every individual LED illuminates the whole surface, the light distribution curves of the LED are overlapping
- sustainable, interchangeable components
- future proof by using standardised Zhaga LED modules
- GreenLine luminaire, outstanding sustainable design

Applications

Hazardous areas zone 2 (gas) and zone 22 (dust), Production, assembly and storage halls in the chemical and pharmaceutical industries, mills, paper mills, etc.



Explosion-protected LED high-bay floodlight

ExDUEVO

nD8302 L320

[Item no. : 83020 0002]

Technical data

Explosion protection

EX-Zone:	2, 22
EX-marking gas:	II 3 G Ex nR IIC T4 Gc
EX-marking dust:	II 3 D Ex tc IIIC T100°C Dc
Primary ignition protection method:	nR
Temperature class:	T4
Surface temperature:	T100°C

Key technical data

Light source:	LED
LED module standard:	Zhaga
Exchangeability:	light source and control gear replaceable by qualified person
Connected load:	192 W
Luminaire luminous flux:	30000 lm
Luminous efficacy:	156 lm/W
Colour temperature:	4000 K
Colour rendering (CRI):	≥ 80
Light colour:	840
Admissible ambient temperature Ta:	-20 °C to +40 °C
Control gear:	2 x ECG, Overload protection, Short circuit protection

Lighting control

Dimmable:	Yes
Dimming method:	DALI (DIMD)
Dimming range:	10 - 100 %

Lighting technology

Light distribution:	wide beam
Photobiological safety:	RG1

Service life

Service life LED:	L70>100000 h (@ Ta max), L80>90000 h (@ Ta max), L80>100000 h (@Ta 25° C)
-------------------	---

Electrical connection

Rated voltage:	220 - 240 V, 50/60 Hz
Terminal clamp:	Cage clamp, 5-polig, 1 - 4 mm ²
Max. no. (with CB B16):	11
CB B10/B13/B20:	7/9/14
CB C10/C13/C16/C20:	11/14/18/22
Cable entries:	M25 (1x), cable gland (1x), Plastic, 8 - 17 mm

Housing

Housing material:	Die-cast aluminium
Varnished:	Yes
Colour:	grey, DB 702

Cover

Cover type/material:	Pane (Safety glass)
Cover characteristic:	clear
Closure:	screwed (Stainless steel (1.4301))

Mounting

Mounting method (accessories possibly needed):	Suspended
Operating position:	downwards radiation
Mounting:	Multi-point

Features/Certificates

Protection class:	I
IP rating:	IP65
IK rating:	IK10
Approval marks:	CE
Energy efficiency class:	D

Dimension/Weight

Length:	877.00 mm
Width/Diameter:	420.00 mm
Height:	100.00 mm
Net weight:	14.50 kg
EAN/GTIN:	4041254325279

Explosion-protected LED high-bay floodlight

ExDUEVO

nD8302 L320

[Item no. : 83020 0002]

Optional accessories/spare parts

Item no.	Item name	Item description
90117 9006	2537 G	cable gland M25 with locknut for Ex-Zone 1/21
90119 9001	2539 G	cable gland M25 with blanking plug and locknut for Ex-Zone 1/21
33001 9004	3301/3302 Y P	1 pair of Y-ropes
33001 9002	DBF 3301/3302	1 pair of brackets for direct ceiling mounting, steel